

(12) STANDARD PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. AU 2001294802 B2

(54) Title
Method and apparatus for casing expansion

(51)⁷ International Patent Classification(s)
E21B 019/16 E21B 043/10
E21B 023/00

(21) Application No: 2001294802

(22) Date of Filing: 2001.09.27

(87) WIPO No: WO02/29199

(30) Priority Data

(31) Number	(32) Date	(33) Country
60237334	2000.10.02	US

(43) Publication Date: 2002.04.15

(43) Publication Journal Date: 2002.06.27

(44) Accepted Journal Date: 2005.12.01

(71) Applicant(s)
Shell Internationale Maatschappij B.V.

(72) Inventor(s)
Waddell, Kevin K.; Filippov, Andrei Gregory; Cook, Robert Lance; Ring, Lev; Zwald, Edwin A.

(74) Agent / Attorney
Davies Collison Cave, Level 15 1 Nicholson Street, MELBOURNE, VIC, 3000

(56) Related Art
US 5348095 US 5667011

2001294802 06 Oct 2005

METHOD AND APPARATUS FOR RADIAL EXPANSION AND/OR COUPLING

Background of the Invention

This invention relates generally to tubular members. For convenience, the invention will be described with reference to wellbore casings that are formed using expandable tubing. However, it will be appreciated that the invention may be applied to other tubular members, such as pipelines and structural supports.

Conventionally, when a wellbore is created, a number of casings are installed in the borehole to prevent collapse of the borehole wall and to prevent undesired outflow of drilling fluid into the formation or inflow of fluid from the formation into the borehole. The borehole is drilled in intervals whereby a casing which is to be installed in a lower borehole interval is lowered through a previously installed casing of an upper borehole interval. As a consequence of this procedure the casing of the lower interval is of smaller diameter than the casing of the upper interval. Thus, the casings are in a nested arrangement with casing diameters decreasing in downward direction. Cement annuli are provided between the outer surfaces of the casings and the borehole wall to seal the casings from the borehole wall. As a consequence of this nested arrangement a relatively large borehole diameter is required at the upper part of the wellbore. Such a large borehole diameter involves increased costs due to heavy casing handling equipment, large drill bits and increased volumes of drilling fluid and drill cuttings. Moreover, increased drilling rig time is involved due to required cement pumping, cement hardening, required equipment changes due to large variations in hole diameters drilled in the course of the well, and the large volume of cuttings drilled and removed.

The present invention is directed to alleviating one or more of the limitations of the existing procedures for forming wellbores and other tubular members.

Summary of the Invention

According to one aspect of the invention, an apparatus for plastically deforming and radially expanding a tubular member is provided that includes means for plastically deforming and radially expanding a first portion of the tubular member to a first outside diameter, and means for plastically deforming and radially expanding a second portion of the tubular member to a second outside diameter. The means for plastically deforming and radially expanding the first portion of the tubular member to the first outside diameter may

be frangible, elastic or inflatable, or it may include rolling means for applying radial pressure to the first portion of the tubular member.

According to another aspect of the present invention, an apparatus for plastically deforming and radially expanding a tubular member is provided that includes a tubular support member including a first fluid passage, an expansion cone coupled to the tubular support member having a second fluid passage fluidically coupled to the first fluid passage and an outer conical surface, a removable annular conical sleeve coupled to the outer conical surface of the expansion cone, an annular expansion cone launcher coupled to the conical sleeve and a lower portion of the tubular member, and a shoe having a valveable passage coupled to an end of the expansion cone launcher. The conical sleeve may be, for example, frangible, elastic or comprised of a plurality of arcuate elements.

According to another aspect of the present invention, a method of plastically deforming and radially expanding a tubular member is provided that includes plastically deforming and radially expanding a portion of the tubular member to a first outside diameter, and plastically deforming and radially expanding another portion of the tubular member to a second outside diameter. In one embodiment, plastically deforming and radially expanding the first portion of the first tubular member comprises applying a radial force to the portion of the tubular member using a conical sleeve. The conical sleeve may be, for example, frangible, elastic or comprised of a plurality of arcuate elements. In another embodiment, plastically deforming and radially expanding the first portion of the first tubular member comprises applying a radial force to the first portion of the first tubular member using an inflatable bladder or using a roller expansion device.

According to another aspect of the present invention, a method of coupling a first tubular member to a second tubular member is provided that includes plastically deforming and radially expanding a first portion of the first tubular member to a first outside diameter, plastically deforming and radially expanding another portion of the first tubular member to a second outside diameter, positioning the second tubular member inside the first tubular member in overlapping relation to the first portion of the first tubular member, plastically deforming and radially expanding the second tubular member to a third outside diameter, and plastically deforming and radially expanding the second tubular member to a fourth outside diameter. The inside diameters of the first and second tubular members after the plastic deformations and radial expansions are substantially equal. The first

outside diameter may be greater than the second outside diameter. In one embodiment, plastically deforming and radially expanding the first portion of the first tubular member comprises applying a radial force to the portion of the tubular member using a conical sleeve. The conical sleeve may be, for example, frangible, elastic or comprised of a plurality of arcuate elements. In another embodiment, plastically deforming and radially expanding the first portion of the first tubular member comprises applying a radial force to the first portion of the first tubular member using an inflatable bladder or using a roller expansion device.

According to another aspect of the present invention, an apparatus for coupling a first tubular member to a second tubular member is provided that includes means for plastically deforming and radially expanding a first portion of the first tubular member to a first outside diameter, means for plastically deforming and radially expanding another portion of the first tubular member to a second outside diameter, means for positioning the second tubular member inside the first tubular member in overlapping relation to the first portion of the first tubular member, means for plastically deforming and radially expanding the second tubular member to a third outside diameter, and means for plastically deforming and radially expanding the second tubular member to a fourth outside diameter. The inside diameters of the first and second tubular members after the plastic deformations and radial expansions are substantially equal. The first outside diameter may be greater than the second outside diameter. In one embodiment, the means for plastically deforming and radially expanding the first portion of the first tubular member comprises means for applying a radial force to the portion of the tubular member using a conical sleeve. The conical sleeve may be, for example, frangible, elastic or comprised of a plurality of arcuate elements. In another embodiment, the means for plastically deforming and radially expanding the first portion of the first tubular member comprises means for applying a radial force to the first portion of the first tubular member using an inflatable bladder or using a roller expansion device.

According to another aspect of the present invention, an apparatus for forming a wellbore casing within a wellbore is provided that includes means for supporting a tubular member within the wellbore, means for plastically deforming and radially expanding a first portion of the tubular member to a first outside diameter, and means for plastically deforming and radially expanding a second portion of the tubular member to a second

2001294802 06 Oct 2005

outside diameter. The means for plastically deforming and radially expanding the first portion of the tubular member to the first outside diameter may be frangible, elastic or inflatable, or it may include rolling means for applying radial pressure to the first portion of the tubular member.

5 According to another aspect of the present invention, an apparatus for forming a wellbore casing within a wellbore is provided that includes a tubular support member including a first fluid passage, an expansion cone coupled to the tubular support member having a second fluid passage fluidically coupled to the first fluid passage and an outer conical surface, a removable annular conical sleeve coupled to the outer conical surface of
10 the expansion cone, an annular expansion cone launcher coupled to the conical sleeve and a lower portion of the tubular member, and a shoe having a valveable passage coupled to an end of the expansion cone launcher. The conical sleeve may be, for example, frangible, elastic or comprised of a plurality of arcuate elements.

According to another aspect of the present invention, a method of forming a
15 wellbore casing within a wellbore is provided that includes supporting a tubular member within a wellbore, plastically deforming and radially expanding a portion of the tubular member to a first outside diameter, and plastically deforming and radially expanding another portion of the tubular member to a second outside diameter. In one embodiment, plastically deforming and radially expanding the first portion of the first tubular member
20 comprises applying a radial force to the portion of the tubular member using a conical sleeve. The conical sleeve may be, for example, frangible, elastic or comprised of a plurality of arcuate elements. In another embodiment, plastically deforming and radially expanding the first portion of the first tubular member comprises applying a radial force to the first portion of the first tubular member using an inflatable bladder or using a roller
25 expansion device.

According to another aspect of the present invention, a method of forming a mono-diameter wellbore casing within a wellbore is provided that includes supporting a first tubular member within the wellbore, plastically deforming and radially expanding a first portion of the first tubular member to a first outside diameter, plastically deforming and
30 radially expanding another portion of the first tubular member to a second outside diameter, positioning the second tubular member inside the first tubular member in overlapping relation to the first portion of the first tubular member, plastically deforming

2001294802 06 Oct 2005

and radially expanding the second tubular member to a third outside diameter, and plastically deforming and radially expanding the second tubular member to a fourth outside diameter. The inside diameters of the first and second tubular members after the plastic deformations and radial expansions are substantially equal. The first outside
5 diameter may be greater than the second outside diameter. In one embodiment, plastically deforming and radially expanding the first portion of the first tubular member comprises applying a radial force to the portion of the tubular member using a conical sleeve. The conical sleeve may be, for example, frangible, elastic or comprised of a plurality of arcuate elements. In another embodiment, plastically deforming and radially expanding the first
10 portion of the first tubular member comprises applying a radial force to the first portion of the first tubular member using an inflatable bladder or using a roller expansion device. The method may further comprise injecting an annular body of a hardenable fluidic sealing material into an annulus between the first tubular member and the wellbore and/or between the second tubular member and the wellbore. The annular body or bodies may be cured.

15 According to another aspect of the present invention, an apparatus for coupling a first tubular member to a second tubular member is provided that includes means for plastically deforming and radially expanding a first portion of the first tubular member to a first outside diameter, means for plastically deforming and radially expanding another portion of the first tubular member to a second outside diameter, means for positioning the
20 second tubular member inside the first tubular member in overlapping relation to the first portion of the first tubular member, means for plastically deforming and radially expanding the second tubular member to a third outside diameter, and means for plastically deforming and radially expanding the second tubular member to a fourth outside diameter. The inside diameters of the first and second tubular members after the plastic deformations and radial
25 expansions are substantially equal. The first outside diameter may be greater than the second outside diameter. In one embodiment, the means for plastically deforming and radially expanding the first portion of the first tubular member comprises means for applying a radial force to the portion of the tubular member using a conical sleeve. The conical sleeve may be, for example, frangible, elastic or comprised of a plurality of arcuate
30 elements. In another embodiment, the means for plastically deforming and radially expanding the first portion of the first tubular member comprises means for applying a radial force to the first portion of the first tubular member using an inflatable bladder or

using a roller expansion device. The apparatus may further comprise means for injecting an annular body of a hardenable fluidic sealing material into an annulus between the first tubular member and the wellbore and/or between the second tubular member and the wellbore. Such apparatus may further comprise means for curing the annular body of
5 hardenable fluidic sealing material.

According to another aspect of the present invention, an apparatus for plastically deforming and radially expanding a tubular member is provided that includes means for providing a lipped portion in a portion of the tubular member, and means for plastically deforming and radially expanding another portion of the tubular member.

10 According to another aspect of the present invention, an apparatus for plastically deforming and radially expanding a tubular member is provided that includes a tubular support member including a first fluid passage, an expansion cone coupled to the tubular support member having a second fluid passage fluidically coupled to the first fluid passage and an outer conical surface, an annular expansion cone launcher including: a first annular
15 portion coupled to a lower portion of the tubular member, a second annular portion coupled to the first annular portion that mates with the outer conical surface of the expansion cone, a third annular portion coupled to the second annular portion having a first outside diameter, and a fourth annular portion coupled to the third annular portion having a second outside diameter, wherein the second outside diameter is less than the first outside
20 diameter, and a shoe having a valveable passage coupled to fourth annular portion of the expansion cone launcher.

According to another aspect of the present invention, a method of plastically deforming and radially expanding a tubular member is provided that includes providing a lipped portion in a portion of the tubular member, and plastically deforming and radially
25 expanding another portion of the tubular member.

According to another aspect of the present invention, a method of coupling a first tubular member to a second tubular member is provided that includes providing a lipped portion in a portion of the first tubular member, plastically deforming and radially expanding another portion of the first tubular member, positioning the second tubular
30 member inside the first tubular member in overlapping relation to the lipped portion of the first tubular member, and plastically deforming and radially expanding the second tubular

2001294802 06 Oct 2005

member. The inside diameters of the first and second tubular members after the plastic deformations and radial expansions are substantially equal.

According to another aspect of the present invention, an apparatus for coupling a first tubular member to a second tubular member is provided that includes means for
5 providing a lipped portion in the first tubular member, means for plastically deforming and radially expanding another portion of the first tubular member, means for positioning the second tubular member inside the first tubular member in overlapping relation to the lipped portion of the first tubular member, and means for plastically deforming and radially
10 expanding the second tubular member. The inside diameters of the first and second tubular members after the plastic deformations and radial expansions are substantially equal.

According to another aspect of the present invention, an apparatus for forming a wellbore casing within a wellbore is provided that includes means for supporting a tubular member within the wellbore, means for providing a lipped portion in the tubular member,
15 and means for plastically deforming and radially expanding another portion of the tubular member to a second outside diameter.

According to another aspect of the present invention, an apparatus for forming a wellbore casing within a wellbore is provided that includes a tubular support member including a first fluid passage, an expansion cone coupled to the tubular support member having a second fluid passage fluidically coupled to the first fluid passage and an outer
20 conical surface, an annular expansion cone launcher including: a first annular portion coupled to a lower portion of the tubular member, a second annular portion coupled to the first annular portion that mates with the outer conical surface of the expansion cone, a third annular portion coupled to the second annular portion having a first outside diameter, and a
25 fourth annular portion coupled to the third annular portion having a second outside diameter, wherein the second outside diameter is less than the first outside diameter, and a shoe having a valveable passage coupled to fourth annular portion of the expansion cone launcher.

According to another aspect of the present invention, a method of forming a wellbore casing in a wellbore is provided that includes supporting a tubular member within
30 the wellbore, providing a lipped portion in a portion of the tubular member, and plastically deforming and radially expanding another portion of the tubular member. The method

may further comprise injecting a hardenable fluidic sealing material in an annulus between the tubular member and the wellbore.

According to another aspect of the present invention, a method of forming a mono-diameter wellbore casing within a wellbore is provided that includes supporting a first tubular member within the wellbore, providing a lipped portion in a portion of the first tubular member, plastically deforming and radially expanding another portion of the first tubular member, positioning the second tubular member inside the first tubular member in overlapping relation to the lipped portion of the first tubular member, and plastically deforming and radially expanding the second tubular member. The inside diameters of the first and second tubular members after the plastic deformations and radial expansions are substantially equal. The method may further comprise injecting a hardenable fluidic sealing material in an annulus between the first tubular member and the wellbore and/or between the second tubular member and the wellbore. The fluidic sealing material may be cured.

According to another aspect of the present invention, an apparatus for forming a mono-diameter wellbore casing within a wellbore is provided that includes means for providing a lipped portion in the first tubular member, means for plastically deforming and radially expanding another portion of the first tubular member, means for positioning the second tubular member inside the first tubular member in overlapping relation to the lipped portion of the first tubular member, and means for plastically deforming and radially expanding the second tubular member. The inside diameters of the first and second tubular members after the plastic deformations and radial expansions are substantially equal. The apparatus may further comprise means for injecting a hardenable fluidic sealing material in an annulus between the first tubular member and the wellbore and/or between the second tubular member and the wellbore. Such apparatus may further comprise means for curing the fluidic sealing material.

According to another aspect of the present invention, an apparatus for plastically deforming and radially expanding a tubular member is provided that includes means for plastically deforming and radially expanding a first end of the tubular member, and means for plastically deforming and radially expanding a second end of the tubular member.

According to another aspect of the present invention, an apparatus for plastically deforming and radially expanding a tubular member is provided that includes a tubular

support member including a first passage, an expansion cone coupled to the tubular support having a second passage fluidically coupled to the first passage and an outer conical surface, an annular expansion cone launcher movably coupled to outer conical surface of the expansion cone, an expandable tubular member coupled to an end of the annular expansion cone launcher, a shoe coupled to another end of the annular expansion cone launcher having a valveable fluid passage, and another annular expansion cone movably coupled to the tubular support member. The annular expansion cones are positioned in opposite orientations. In one embodiment, the annular expansion cone is adapted to plastically deform and radially expand a first end of the expandable tubular member and the other annular expansion cone is adapted to plastically deform and radially expand a second end of the expandable tubular member. The apparatus may further comprise an anchoring member coupled to the tubular support member adapted to hold the expandable tubular.

According to another aspect of the present invention, an apparatus for forming a wellbore casing within a wellbore is provided that includes a tubular support member including a first passage, an expansion cone coupled to the tubular support having a second passage fluidically coupled to the first passage and an outer conical surface, an annular expansion cone launcher movably coupled to outer conical surface of the expansion cone, an expandable tubular member coupled to an end of the annular expansion cone launcher, a shoe coupled to another end of the annular expansion cone launcher having a valveable fluid passage, and another annular expansion cone movably coupled to the tubular support member. The annular expansion cones are positioned in opposite orientations. In one embodiment, the annular expansion cone is adapted to plastically deform and radially expand a first end of the expandable tubular member and the other annular expansion cone is adapted to plastically deform and radially expand a second end of the expandable tubular member. The apparatus may further comprise an anchoring member coupled to the tubular support member adapted to hold the expandable tubular.

According to another aspect of the present invention, an apparatus for bridging an axial gap between opposing pairs of wellbore casing within a wellbore is provided that includes means for supporting a tubular member in overlapping relation to the opposing ends of the wellbore casings, means for plastically deforming and radially expanding the

tubular member, and means for plastically deforming and radially expanding the tubular member and the opposing ends of the wellbore casings.

According to another aspect of the present invention, a method of bridging an axial gap between opposing pairs of wellbore casing within a wellbore is provided that includes supporting a tubular member in overlapping relation to the opposing ends of the wellbore casings, plastically deforming and radially expanding the tubular member, and plastically deforming and radially expanding the tubular member and the opposing ends of the wellbore casings.

According to another aspect of the present invention, a method of forming a structure having desired strength characteristics is provided that includes providing a first tubular member, and plastically deforming and radially expanding additional tubular members onto the interior surface of the first tubular member until the desired strength characteristics are achieved.

According to another aspect of the present invention, a method of forming a wellbore casing within a wellbore having desired strength characteristics is provided that includes plastically deforming and radially expanding a first tubular member within the wellbore, and plastically deforming and radially expanding additional tubular members onto the interior surface of the first tubular member until the desired strength characteristics are achieved.

According to another aspect of the present invention, a method of coupling a first tubular member to a second tubular member, the first tubular member having an original outside diameter OD_0 and an original wall thickness t_0 , is provided that includes plastically deforming and radially expanding a first portion of the first tubular member to a first outside diameter, plastically deforming and radially expanding another portion of the first tubular member to a second outside diameter, positioning the second tubular member inside the first tubular member in overlapping relation to the first portion of the first tubular member, plastically deforming and radially expanding the second tubular member to a third outside diameter, and plastically deforming and radially expanding the second tubular member to a fourth outside diameter. The inside diameters of the first and second tubular members after the plastic deformations and radial expansions are substantially equal, and the ratio of the original outside diameter OD_0 of the first tubular member to the original wall thickness t_0 of the first tubular member is greater than or equal to 16.

2001294802 06 Oct 2005

According to another aspect of the present invention, a method of forming a mono-diameter wellbore casing is provided that includes positioning a first tubular member within a wellbore, the first tubular member having an original outside diameter OD_0 and an original wall thickness t_0 , plastically deforming and radially expanding a first portion of the first tubular member to a first outside diameter, plastically deforming and radially expanding another portion of the first tubular member to a second outside diameter, positioning the second tubular member inside the first tubular member in overlapping relation to the first portion of the first tubular member, plastically deforming and radially expanding the second tubular member to a third outside diameter, and plastically deforming and radially expanding the second tubular member to a fourth outside diameter. The inside diameters of the first and second tubular members after the plastic deformations and radial expansions are substantially equal, and the ratio of the original outside diameter OD_0 of the first tubular member to the original wall thickness t_0 of the first tubular member is greater than or equal to 16.

According to another aspect of the present invention, an apparatus is provided that includes a plastically deformed and radially expanded tubular member having a first portion having a first outside diameter and a remaining portion having a second outside diameter. The ratio of the original outside diameter OD_0 of the first tubular member to the original wall thickness t_0 of the first tubular member is greater than or equal to 16.

According to another aspect of the present invention, an apparatus is provided that includes a plastically deformed and radially expanded first tubular member having a first portion having a first outside diameter and a remaining portion having a second outside diameter, and a plastically deformed and radially expanded second tubular member coupled to the first portion of the first tubular member. The ratio of the original outside diameter OD_0 of the first tubular member to the original wall thickness t_0 of the first tubular member is greater than or equal to 16. In one embodiment, the inside diameters of the first and second tubular members are substantially equal.

According to another aspect of the present invention, a wellbore casing formed in a wellbore is provided that includes a plastically deformed and radially expanded first tubular member having a first portion having a first outside diameter and a remaining portion having a second outside diameter, and a plastically deformed and radially expanded second tubular member coupled to the first portion of the first tubular member.

The ratio of the original outside diameter OD_0 of the first tubular member to the original wall thickness t_0 of the first tubular member is greater than or equal to 16. In one embodiment, the inside diameters of the first and second tubular members are substantially equal.

- 5 According to another aspect of the present invention, an apparatus is provided that includes a plastically deformed and radially expanded tubular member. The ratio of the original outside diameter OD_0 of the tubular member to the original wall thickness t_0 of the tubular member is greater than or equal to 16.

- 10 According to another aspect of the present invention there is provided an apparatus for plastically deforming and radially expanding a tubular member, comprising: means for coupling a first expansion cone to a second expansion cone; means for plastically deforming and radially expanding a first portion of the tubular member to a first outside diameter using the first and second expansion cones; means for plastically deforming and radially expanding a second portion of the tubular member to a second outside diameter using the second expansion cone; and means for decoupling the first and second expansion cones prior to plastically deforming and radially expanding the second portion of the tubular member to the second outside diameter; wherein the first outside diameter is greater than the second outside diameter.

- 15 According to another aspect of the present invention there is provided a method of plastically deforming and radially expanding a tubular member, comprising: plastically deforming and radially expanding a portion of the tubular member to a first outside diameter using a first expansion cone coupled to a second expansion cone; decoupling the first and second expansion cones; and plastically deforming and radially expanding another portion of the tubular member to a second outside diameter using the second expansion cone; wherein the first outside diameter is greater than the second outside diameter.

- 20 According to another aspect of the present invention there is provided a method of coupling a first tubular member to a second tubular member, comprising: plastically deforming and radially expanding a first portion of the first tubular member to a first outside diameter using a first expansion cone coupled to a second expansion cone; decoupling the first and second expansion cones; plastically deforming and radially expanding another portion of the first tubular member to a second outside diameter using the second expansion cone; positioning the second tubular member inside the first tubular

member in overlapping relation to the first portion of the first tubular member; plastically deforming and radially expanding the second tubular member to a third outside diameter; and plastically deforming and radially expanding the second tubular member to a fourth outside diameter; wherein the first outside diameter is greater than the second outside diameter; and wherein the inside diameters of the first and second tubular members after the plastic deformations and radial expansions are substantially equal.

According to another aspect of the present invention there is provided an apparatus for coupling a first tubular member to a second tubular member, comprising: means for plastically deforming and radially expanding a first portion of the first tubular member to a first outside diameter using a first expansion cone coupled to a second expansion cone; means for decoupling the first expansion cone from the second expansion cone; means for plastically deforming and radially expanding another portion of the first tubular member to a second outside diameter using the second expansion cone; means for positioning the second tubular member inside the first tubular member in overlapping relation to the first portion of the first tubular member; means for plastically deforming and radially expanding the second tubular member to a third outside diameter; and means for plastically deforming and radially expanding the second tubular member to a fourth outside diameter; wherein the first outside diameter is greater than the second outside diameter; and wherein the inside diameters of the first and second tubular members after the plastic deformations and radial expansions are substantially equal.

According to another aspect of the present invention there is provided an apparatus for forming a wellbore casing within a wellbore, comprising: means for supporting a tubular member within the wellbore; means for plastically deforming and radially expanding a first portion of the tubular member to a first outside diameter using a first expansion cone coupled to a second expansion cone; means for decoupling the first and second expansion cones; and means for plastically deforming and radially expanding a second portion of the tubular member to a second outside diameter using the second expansion cone; wherein the first outside diameter is greater than the second outside diameter.

According to another aspect of the present invention there is provided a method of forming a wellbore casing within a wellbore, comprising: supporting a tubular member within a wellbore; plastically deforming and radially expanding a portion of the tubular member to a first outside diameter using a first expansion cone coupled to a second

expansion cone; decoupling the first and second expansion cones; and plastically deforming and radially expanding another portion of the tubular member to a second outside diameter using the second expansion cone; wherein the first outside diameter is greater than the second outside diameter.

- 5 According to another aspect of the present invention there is provided a method of forming a mono-diameter wellbore casing within a wellbore, comprising: supporting a first tubular member within the wellbore; plastically deforming and radially expanding a first portion of the first tubular member to a first outside diameter using a first expansion cone coupled to a second expansion cone; decoupling the first and second expansion cones;
- 10 plastically deforming and radially expanding another portion of the first tubular member to a second outside diameter using the second expansion cone; positioning the second tubular member inside the first tubular member in overlapping relation to the first portion of the first tubular member; plastically deforming and radially expanding the second tubular member to a third outside diameter; and plastically deforming and radially expanding the
- 15 second tubular member to a fourth outside diameter; wherein the first outside diameter is greater than the second outside diameter; and wherein the inside diameters of the first and second tubular members after the plastic deformations and radial expansions are substantially equal.

- According to another aspect of the present invention there is provided an apparatus
- 20 for coupling a first tubular member to a second tubular member, comprising: means for plastically deforming and radially expanding a first portion of the first tubular member to a first outside diameter using a first expansion cone coupled to a second expansion cone; means for decoupling the first and second expansion cones; means for plastically deforming and radially expanding another portion of the first tubular member to a second
- 25 outside diameter using the second expansion cone; means for positioning the second tubular member inside the first tubular member in overlapping relation to the first portion of the first tubular member; means for plastically deforming and radially expanding the second tubular member to a third outside diameter; and means for plastically deforming and radially expanding the second tubular member to a fourth outside diameter; wherein
- 30 the first outside diameter is greater than the second outside diameter; and wherein the inside diameters of the first and second tubular members after the plastic deformations and radial expansions are substantially equal.

Brief Description of the Drawings

Fig. 1a is a cross sectional illustration of a wellbore including a preexisting wellbore casing.

Fig. 1b is a cross-sectional illustration of the placement of an embodiment of an apparatus for radially expanding a tubular member into the wellbore of Fig. 1a.

Fig. 1c is a cross-sectional illustration of the injection of fluidic materials through the apparatus of Fig. 1b.

Fig. 1d is a cross-sectional illustration of the injection of hardenable fluidic sealing materials through the apparatus of Fig. 1c.

Fig. 1e is a cross-sectional illustration of the pressurization of the region below the expansion cone of the apparatus of Fig. 1d.

Fig. 1f is a cross-sectional illustration of the continued pressurization of the region below the expansion cone of the apparatus of Fig. 1e.

Fig. 1g is a cross-sectional illustration of the continued pressurization of the region below the expansion cone of the apparatus of Fig. 1f following the removal of the over-expansion sleeve.

Fig. 1h is a cross-sectional illustration of the completion of the radial expansion of the expandable tubular member of the apparatus of Fig. 1g.

Fig. 1i is a cross-sectional illustration of the drilling out of a new section of the wellbore below the apparatus of Fig. 1h.

Fig. 1j is a cross-sectional illustration of the radial expansion of another expandable tubular member that overlaps with the apparatus of Fig. 1i.

Fig. 1k is a cross-sectional illustration of the secondary radial expansion of the other expandable tubular member of the apparatus of Fig. 1i.

Fig. 1l is a cross-sectional illustration of the completion of the secondary radial expansion of the other expandable tubular member of Fig. 1k to form a mono-diameter wellbore casing.

Fig. 2a is a cross sectional illustration of a wellbore including a preexisting wellbore casing.

Fig. 2b is a cross-sectional illustration of the placement of an embodiment of an apparatus for radially expanding a tubular member into the wellbore of Fig. 2a.

Fig. 2c is a cross-sectional illustration of the injection of fluidic materials through the apparatus of Fig. 2b.

Fig. 2d is a cross-sectional illustration of the injection of hardenable fluidic sealing materials through the apparatus of Fig. 2c.

5 Fig. 2e is a cross-sectional illustration of the pressurization of the region below the expansion cone of the apparatus of Fig. 2d.

Fig. 2f is a cross-sectional illustration of the continued pressurization of the region below the expansion cone of the apparatus of Fig. 2e.

10 Fig. 2g is a cross-sectional illustration of the completion of the radial expansion of the expandable tubular member of the apparatus of Fig. 2f.

Fig. 2h is a cross-sectional illustration of the drilling out of a new section of the wellbore below the apparatus of Fig. 2g.

Fig. 2i is a cross-sectional illustration of the radial expansion of another expandable tubular member that overlaps with the apparatus of Fig. 2h.

15 Fig. 2j is a cross-sectional illustration of the secondary radial expansion of the other expandable tubular member of the apparatus of Fig. 2i.

Fig. 2k is a cross-sectional illustration of the completion of the secondary radial expansion of the other expandable tubular member of Fig. 2j to form a mono-diameter wellbore casing.

20 Fig. 3 is a cross-sectional illustration of the apparatus of Fig. 2b illustrating the design and construction of the over-expansion insert.

Fig. 3a is a cross-sectional illustration of an alternative embodiment of the over-expansion insert of Fig. 3.

25 Fig. 4 is a cross-sectional illustration of an alternative embodiment of the apparatus of Fig. 2b including a resilient hook for retrieving the over-expansion insert.

Fig. 5a is a cross-sectional illustration of a wellbore including a preexisting wellbore casing.

Fig. 5b is a cross-sectional illustration of the formation of a new section of wellbore casing in the wellbore of Fig. 5a.

30 Fig. 5c is a fragmentary cross-sectional illustration of the placement of an inflatable bladder into the new section of the wellbore casing of Fig. 5b.

Fig. 5d is a fragmentary cross-sectional illustration of the inflation of the inflatable bladder of Fig. 5c.

Fig. 5e is a cross-sectional illustration of the new section of wellbore casing of Fig. 5d after over-expansion.

5 Fig. 5f is a cross-sectional illustration of the new section of wellbore casing of Fig. 5e after drilling out a new section of the wellbore.

Fig. 5g is a cross-sectional illustration of the formation of a mono-diameter wellbore casing that includes the new section of the wellbore casing and an additional section of wellbore casing.

10 Fig. 6a is a cross-sectional illustration of a wellbore including a preexisting wellbore casing.

Fig. 6b is a cross-sectional illustration of the formation of a new section of wellbore casing in the wellbore of Fig. 6a.

15 Fig. 6c is a fragmentary cross-sectional illustration of the placement of a roller radial expansion device into the new section of the wellbore casing of Fig. 6b.

Fig. 6d is a cross-sectional illustration of the new section of wellbore casing of Fig. 6c after over-expansion.

Fig. 6e is a cross-sectional illustration of the new section of wellbore casing of Fig. 6d after drilling out a new section of the wellbore.

20 Fig. 6f is a cross-sectional illustration of the formation of a mono-diameter wellbore casing that includes the new section of the wellbore casing and an additional section of wellbore casing.

Fig. 7a is a cross sectional illustration of a wellbore including a preexisting wellbore casing.

25 Fig. 7b is a cross-sectional illustration of the placement of an embodiment of an apparatus for radially expanding a tubular member into the wellbore of Fig. 7a.

Fig. 7c is a cross-sectional illustration of the injection of fluidic materials through the apparatus of Fig. 7b.

30 Fig. 7d is a cross-sectional illustration of the injection of hardenable fluidic sealing materials through the apparatus of Fig. 7c.

Fig. 7e is a cross-sectional illustration of the pressurization of the region below the expansion cone of the apparatus of Fig. 7d.

Fig. 7f is a cross-sectional illustration of the continued pressurization of the region below the expansion cone of the apparatus of Fig. 7e.

Fig. 7g is a cross-sectional illustration of the completion of the radial expansion of the expandable tubular member of the apparatus of Fig. 7f.

5 Fig. 7h is a cross-sectional illustration of the drilling out of a new section of the wellbore below the apparatus of Fig. 7g.

Fig. 7i is a cross-sectional illustration of the completion of the radial expansion of another expandable tubular member to form a mono-diameter wellbore casing.

10 Fig. 8a is cross-sectional illustration of an wellbore including a preexisting section of wellbore casing having a recessed portion.

Fig. 8b is a cross-sectional illustration of the placement of an apparatus for radially expanding a tubular member within the wellbore of Fig. 8a.

Fig. 8c is a cross-sectional illustration of the injection of fluidic materials through the apparatus of Fig. 8b.

15 Fig. 8d is a cross-sectional illustration of the injection of a hardenable fluidic sealing material through the apparatus of Fig. 8c.

Fig. 8e is cross-sectional illustration of the isolation of the region below the expansion cone and within the expansion cone launcher of the apparatus of Fig. 8d.

20 Fig. 8f is a cross-sectional illustration of the plastic deformation and radial expansion of the upper portion of the expandable tubular member of the apparatus of Fig. 8e.

Fig. 8g is a cross-sectional illustration of the removal of the upper expansion cone from the wellbore of fig. 8f.

25 Fig. 8h is a cross-sectional illustration of the continued pressurization of the region below the expansion cone of the apparatus of Fig. 8g to thereby plastically deform and radially expand the expansion cone launcher and expandable tubular member.

Fig. 8i is a cross-sectional illustration of the completion of the initial radial expansion process of the apparatus of Fig. 8h.

30 Fig. 8j is a cross-sectional illustration of the further radial expansion of the apparatus of Fig. 8i in order to form a mono-diameter wellbore casing.

Fig. 9a is a cross-sectional illustration of a wellbore including upper and lower preexisting wellbore casings that are separated by an axial gap.

Fig. 9b is a cross-sectional illustration of the coupling of a tubular member to the opposing ends of the wellbore casings of Fig. 9a.

Fig. 9c is a fragmentary cross-sectional illustration of the placement of a radial expansion device into the tubular member of Fig. 9b.

5 Fig. 9d is a fragmentary cross-sectional illustration of the actuation of the radial expansion device of Fig. 9c.

Fig. 9e is a cross-sectional of a mono-diameter wellbore casing generated by the actuation of the radial expansion device of Fig. 9d.

10 Fig. 10 is a cross-sectional illustration of a mono-diameter wellbore casing that includes a plurality of layers of radially expanded tubular members along at least a portion of the its length.

Fig. 11a is a cross-sectional illustration of a wellbore including a casing formed by plastically deforming and radially expanding a first tubular member.

15 Fig. 11b is a cross-sectional illustration of a wellbore including another casing coupled to the preexisting casing by plastically deforming and radially expanding a second tubular member.

Fig. 11c is a cross-sectional illustration of a mono-diameter wellbore casing formed by radially expanding the second tubular member a second time.

2001294802 06 Oct 2005

Detailed Description

Several embodiments of methods and apparatus for forming a mono-diameter wellbore casing are disclosed. In several alternative embodiments, the methods and apparatus may be used for form or repair mono-diameter wellbore casings, pipelines, or structural supports. Furthermore, while the present illustrative embodiments are described with reference to the formation of mono-diameter wellbore casings, the teachings of the present disclosure have general application to the formation or repair of wellbore casings, pipelines, and structural supports.

Referring initially to Fig. 1a, a wellbore 10 includes a preexisting wellbore casing 15. The wellbore 10 may be oriented in any orientation from the vertical to the horizontal. The preexisting wellbore casing 15 may be coupled to the upper portion of the wellbore 10 using any number of conventional methods. In a preferred embodiment, the wellbore casing 15 is coupled to the upper portion of the wellbore 10 using one or more of the methods and apparatus disclosed in one or more of the following: (1) U.S. patent 6497289, (2) Australian patent application AU-A-16417/00, (3) U.S. patent 6823937, (4) U.S. patent 6328113, (5) U.S. patent 6640903, (6) U.S. patent 6568471, (7) U.S. patent 6575240, (8) U.S. patent 6557640, (9) U.S. patent 6604763, (10) International patent application WO 01/04535, (11) International patent application WO 01/33037, (12) U.S. patent 6564875, (13) U.S. patent 6695012, (14) U.S. patent application US-A-2003-0121558, (15) U.S. patent application US-A-2004-0033906, (16) U.S. patent application US-A-2003-0116325, and (17) U.S. patent application US-A-2004-0045718, the disclosures of which are incorporated herein by reference. More generally, the preexisting wellbore casing 15 may be coupled to another preexisting wellbore casing and/or may include one or more concentrically positioned tubular members.

Referring to Fig. 1b, an apparatus 100 for radially expanding a tubular member may then be positioned within the wellbore 10. The apparatus 100 includes a tubular support member 105 defining a passage 110 for conveying fluidic materials. An expansion cone 115 defining a passage 120 and having an outer conical surface 125 for

radially expanding tubular members is coupled to an end of the tubular support member 105. An annular conical over-expansion sleeve 130 mates with and is removably coupled to the outer conical surface 125 of the expansion cone 115. In several alternative embodiments, the over-expansion sleeve 130 is fabricated from

5 frangible materials such as, for example, ceramic materials, in order to facilitate the removal of the over-expansion sleeve during operation of the apparatus 100. In this manner, the amount of radial expansion provided by the apparatus may be decreased following the removal of the over-expansion sleeve 130.

An expansion cone launcher 135 is movably coupled to and supported by the

10 expansion cone 115 and the over-expansion sleeve 130. The expansion cone launcher 135 include an upper portion having an upper outer diameter, an intermediate portion that mates with the expansion cone 115 and the over-expansion sleeve 130, an a lower portion having a lower outer diameter. The lower outer diameter is greater than the upper outer diameter. A shoe 140 defining a valveable passage 145 is coupled to the

15 lower portion of the expansion cone launcher 135. In a preferred embodiment, the valveable passage 145 may be controllably closed in order to fluidically isolate a region 150 below the expansion cone 115 and bounded by the lower portion of the expansion cone launcher 135 and the shoe 140 from the region outside of the apparatus 100.

An expandable tubular member 155 is coupled to the upper portion of the

20 expansion cone launcher 135. One or more sealing members 160a and 160b are coupled to the exterior of the upper portion of the expandable tubular member 155. In several alternative embodiments, the sealing members 160a and 160b may include elastomeric elements and/or metallic elements and/or composite elements. In several alternative embodiments, one or more anchoring elements may substituted for, or used

25 in addition to, the sealing members 160a and 160b.

In a preferred embodiment, the support member 105, the expansion cone 115, the expansion cone-launcher 135, the shoe 140, and the expandable tubular member 155 are provided substantially as disclosed in one or more of the following: (1) U.S. patent 6497289, (2) Australian patent application AU-A-16417/00, (3) U.S. patent

6823937, (4) U.S. patent 6328113, (5) U.S. patent 6640903, (6) U.S. patent 6568471, (7) U.S. patent 6575240, (8) U.S. patent 6557640, (9) U.S. patent 6604763, (10) International patent application WO 01/04535, (11) International patent application WO 01/33037, (12) U.S. patent 6564875, (13) U.S. patent 6695012, (14) U.S. patent application US-A-2003-0121558, (15) U.S. patent application US-A-2004-0033906, (16) U.S. patent application US-A-2003-0116325, and (17) U.S. patent application US-A-2004-0045718, the disclosures of which are incorporated herein by reference.

As illustrated in Fig. 1b, in a preferred embodiment, during placement of the apparatus 100 within the wellbore 10, fluidic materials 165 within the wellbore 10 are conveyed through the apparatus 100 through the passages 110, 120 and 145 to a location above the apparatus 100. In this manner, surge pressures during placement of the apparatus 100 within the wellbore 10 are reduced. In a preferred embodiment, the apparatus 100 is initially positioned within the wellbore 10 such that the top portion of the tubular member 155 overlaps with the preexisting casing 15. In this manner, the upper portion of the expandable tubular member 155 may be radially expanded into contact with and coupled to the preexisting casing 15. As will be recognized by persons having ordinary skill in the art, the precise initial position of the expandable tubular member 155 will vary as a function of the amount of radial expansion, the amount of axial shrinkage during radial expansion, and the material properties of the expandable tubular member.

As illustrated in Fig. 1c, a fluidic material 170 may then be injected through the apparatus 100 through the passages 110, 120, and 145 in order to test the proper operation of these passages.

As illustrated in Fig. 1d, a hardenable fluidic sealing material 175 may then be injected through the apparatus 100 through the passages 110, 120 and 145 into the annulus between the apparatus and the wellbore 10. In this manner, an annular barrier to fluid migration into and out of the wellbore 10 may be formed around the radially expanded expansion cone launcher 135 and expandable tubular member 155. The hardenable fluidic sealing material may include, for example, a cement mixture. In

2001294802 06 Oct 2005

several alternative embodiments, the injection of the hardenable fluidic sealing material 175 may be omitted. In several alternative embodiments, the hardenable fluidic sealing material 175 is compressible, before, during and/or after, the curing process.

As illustrated in Fig. 1e, a non-hardenable fluidic material 180 may then be injected
5 into the apparatus through the passages 110 and 120. A ball plug 185, or other

similar device, may then be injected with the fluidic material 180 to thereby seal off the passage 145. In this manner, the region 150 may be pressurized by the continued injection of the fluidic material 180 into the apparatus 100.

As illustrated in Fig. 1f, the continued injection of the fluidic material 180 into the apparatus 100 causes the expansion cone launcher 135 and expandable tubular member 155 to be plastically deformed and radially expanded off of the over-expansion sleeve 130. In this manner, the expansion cone 115 and over-expansion sleeve 130 are displaced relative to the expansion cone launcher 135 and expandable tubular member 155 in the axial direction.

After a predetermined time period and/or after a predetermined axial displacement of the expansion cone 115 relative to the expansion cone launcher 135 and expandable tubular member 155, the over-expansion sleeve 130 may be removed from the outer conical surface 125 of the expansion cone 115 by the application of a predetermined upward shock load to the support member 105. In a preferred embodiment, the shock load causes the frangible over-expansion sleeve 130 to fracture into small pieces that are then forced off of the outer conical surface 125 of the expansion cone 115 by the continued pressurization of the region 150. In a preferred embodiment, the pieces of the over-expansion sleeve 130 are pulverized into grains of material by the continued pressurization of the region 150.

Referring to Fig. 1g, following the removal of the frangible over-expansion sleeve 130, the continued pressurization of the region 150 causes the expandable tubular member 155 to be plastically deformed and radially expanded and extruded off of the outer conical surface 125 of the expansion cone 115. Note that the amount of radial expansion provided by the outer conical surface 125 of expansion cone 115 is less than the amount of radial expansion provided by the combination of the over-expansion sleeve 130 and the expansion cone 115. In this manner, as illustrated in Fig. 1h, a recess 185 is formed in the radially expanded tubular member 155.

After completing the plastic deformation and radial expansion of the tubular member 155, the hardenable fluidic sealing material is allowed to cure to thereby form an annular body 190 that provides a barrier to fluid flow into or out of the wellbore 10.

Referring to Fig. 1i, the shoe 140 may then removed by drilling out the shoe using a conventional drilling device. A new section of the wellbore 10 may also be drilled out in

order to permit additional expandable tubular members to be coupled to the bottom portion of the plastically deformed and radially expanded tubular member 155.

Referring to Fig. 1j, a tubular member 200 may then be plastically deformed and radially expanded using any number of conventional methods of radially expanding a tubular member. In a preferred embodiment, the upper portion of the radially expanded tubular member 200 overlaps with and mates with the recessed portion 185 of the tubular member 155. In a preferred embodiment, one or more sealing members 205 are coupled to the exterior surface of the upper portion of the tubular member 200. In a preferred embodiment, the sealing members 205 seal the interface between the upper portion of the tubular member 200 and the recessed portion 185 of the tubular member 155. In several alternative embodiments, the sealing members 205 may include elastomeric elements and/or metallic elements and/or composite elements. In several alternative embodiments, one or more anchoring elements may substituted for, or used in addition to, the sealing members 205. In a preferred embodiment, an annular body 210 of a hardenable fluidic sealing material is also formed around the tubular member 200 using one or more conventional methods.

In a preferred embodiment, the tubular member 200 is plastically deformed and radially expanded, and the annular body 210 is formed using one or more of the apparatus and methods disclosed in the following: (1) U.S. patent 6497289, (2) Australian patent application AU-A-16417/00, (3) U.S. patent 6823937, (4) U.S. patent 6328113, (5) U.S. patent 6640903, (6) U.S. patent 6568471, (7) U.S. patent 6575240, (8) U.S. patent 6557640, (9) U.S. patent 6604763, (10) International patent application WO 01/04535, (11) International patent application WO 01/33037, (12) U.S. patent 6564875, (13) U.S. patent 6695012, (14) U.S. patent application US-A-2003-0121558, (15) U.S. patent application US-A-2004-0033906, (16) U.S. patent application US-A-2003-0116325, and (17) U.S. patent application US-A-2004-0045718, the disclosures of which are incorporated herein by reference.

In an alternative embodiment, the annular body 210 may be omitted. In several alternative embodiments, the annular body 210 may be radially compressed before, during and/or after curing.

Referring to Fig. 1k, an expansion cone 215 may then be driven in a downward direction by fluid pressure and/or by a support member 220 to plastically deform and radially expand the tubular member 200 such that the interior diameter of the tubular members 155 and 200 are substantially equal. In this manner, as illustrated in Fig. 1l, a mono-diameter wellbore casing may be formed.

Referring to Figs. 2a and 2b, in an alternative embodiment, an apparatus 300 for radially expanding a tubular member may then be positioned within the wellbore 10. The apparatus 300 includes a tubular support member 305 defining a passage 310 for conveying fluidic materials. An expansion cone 315 defining a passage 320 and having an outer conical surface 325 for radially expanding tubular members is coupled to an end of the tubular support member 305. An annular conical over-expansion insert 330 mates with and is removably coupled to the outer conical surface 325 of the expansion cone 315.

An expansion cone launcher 335 is movably coupled to and supported by the expansion cone 315 and the over-expansion insert 330. The expansion cone launcher 335 includes an upper portion having an upper outer diameter, an intermediate portion that mates with the expansion cone 315 and the over-expansion insert 330, and a lower portion having a lower outer diameter. The lower outer diameter is greater than the upper outer diameter. A shoe 340 defining a valveable passage 345 is coupled to the lower portion of the expansion cone launcher 335. In a preferred embodiment, the valveable passage 345 may be controllably closed in order to fluidically isolate a region 350 below the expansion cone 315 and bounded by the lower portion of the expansion cone launcher 335 and the shoe 340 from the region outside of the apparatus 300.

In a preferred embodiment, as illustrated in Fig. 3, the over-expansion insert 330 includes a plurality of spaced-apart arcuate inserts 330a, 330b, 330c and 330d that are positioned between the outer conical surface 325 of the expansion cone 315 and the

inner surface of the intermediate portion of the expansion cone launcher 335. In this manner, the relative axial displacement of the expansion cone 315 and the expansion cone launcher 335 will cause the expansion cone to over-expand the intermediate portion of the expansion cone launcher. In this manner, a recess may be formed in the

5 radially expanded expansion cone launcher 335. In several alternative embodiments, the inserts 330a, 330b, 330c, and 330d fall out of the recess and/or are removed from the recess using a conventional retrieval tool upon the completion of the radial expansion process.

In an alternative embodiment, as illustrated in Fig. 3a, the over expansion insert

10 330 further includes intermediate resilient members 331a, 331b, 331c, and 331d for resiliently coupling the inserts 330a, 330b, 330c, and 330d. In this manner, upon the completion of the radial expansion process, the resilient force exerted by the resilient members 331 causes the over-expansion insert to collapse in the radial direction and thereby fall out of the recess.

15 An expandable tubular member 355 is coupled to the upper portion of the expansion cone launcher 335. One or more sealing members 360a and 360b are coupled to the exterior of the upper portion of the expandable tubular member 355. In several alternative embodiments, the sealing members 360a and 360b may include elastomeric elements and/or metallic elements and/or composite elements. In several

20 alternative embodiments, one or more anchoring elements may substituted for, or used in addition to, the sealing members 360a and 360b.

In a preferred embodiment, the support member 305, the expansion cone 315, the expansion cone launcher 335, the shoe 340, and the expandable tubular member 355 are provided substantially as disclosed in one or more of the following: (1) U.S.

25 patent 6497289, (2) Australian patent application AU-A-16417/00, (3) U.S. patent 6823937, (4) U.S. patent 6328113, (5) U.S. patent 6640903, (6) U.S. patent 6568471, (7) U.S. patent 6575240, (8) U.S. patent 6557640, (9) U.S. patent 6604763, (10) International patent application WO 01/04535, (11) International patent application WO 01/33037, (12) U.S. patent 6564875, (13) U.S. patent 6695012, (14) U.S. patent

2001294802 06 Oct 2005

application US-A-2003-0121558, (15) U.S. patent application US-A-2004-0033906, (16) U.S. patent application US-A-2003-0116325, and (17) U.S. patent application US-A-2004-0045718, the disclosures of which are incorporated herein by reference.

As illustrated in Fig. 2b, in a preferred embodiment, during placement of the apparatus 300 within the wellbore 10, fluidic materials 365 within the wellbore 10 are conveyed through the apparatus 300 through the passages 310, 320 and 345 to a location above the apparatus 300. In this manner, surge pressures during placement of the apparatus 300 within the wellbore 10 are reduced. In a preferred embodiment, the apparatus 300 is initially positioned within the wellbore 10 such that the top portion of the tubular member 355 overlaps with the preexisting casing 15. In this manner, the upper

portion of the expandable tubular member 355 may be radially expanded into contact with and coupled to the preexisting casing 15. As will be recognized by persons having ordinary skill in the art, the precise initial position of the expandable tubular member 355 will vary as a function of the amount of radial expansion, the amount of axial shrinkage
5 during radial expansion, and the material properties of the expandable tubular member.

As illustrated in Fig. 2c, a fluidic material 370 may then be injected through the apparatus 300 through the passages 310, 320, and 345 in order to test the proper operation of these passages.

As illustrated in Fig. 2d, a hardenable fluidic sealing material 375 may then be
10 injected through the apparatus 300 through the passages 310, 320 and 345 into the annulus between the apparatus and the wellbore 10. In this manner, an annular barrier to fluid migration into and out of the wellbore 10 may be formed around the radially expanded expansion cone launcher 335 and expandable tubular member 355. The hardenable fluidic sealing material may include, for example, a cement mixture. In several alternative
15 embodiments, the injection of the hardenable fluidic sealing material 375 may be omitted. In several alternative embodiments, the hardenable fluidic sealing material 375 is compressible, before, during and/or after, the curing process.

As illustrated in Fig. 2e, a non-hardenable fluidic material 380 may then be injected into the apparatus through the passages 310 and 320. A ball plug 385, or other
20 similar device, may then be injected with the fluidic material 380 to thereby seal off the passage 345. In this manner, the region 350 may be pressurized by the continued injection of the fluidic material 380 into the apparatus 300.

As illustrated in Fig. 2f, the continued injection of the fluidic material 380 into the apparatus 300 causes the expansion cone launcher 335 to be plastically deformed and
25 radially expanded off of the over-expansion insert 330. In this manner, the expansion cone 315 is displaced relative to the expansion cone launcher 335 and expandable tubular member 355 in the axial direction.

Once the radial expansion process has progressed beyond the over-expansion insert 330, the radial expansion of the expansion cone launcher 335 and expandable tubular
30 member 355 is provided solely by the outer conical surface 325 of the expansion cone 315. Note that the amount of radial expansion provided by the outer conical surface 325 of expansion cone 315 is less than the amount of radial expansion provided by the

combination of the over-expansion insert 330 and the expansion cone 315. In this manner, as illustrated in Fig. 2g, a recess 390 is formed in the radially expanded tubular member 355.

In several alternative embodiments, the over-expansion insert 330 is removed from the recess 390 by falling out and/or removal using a conventional retrieval tool. In an alternative embodiment, the resilient force provided by the resilient members 331a, 331b, 331c, and 331d cause the insert 330 to collapse in the radial direction and thereby fall out of the recess 390. In an alternative embodiment, as illustrated in Fig. 4, one or more resilient hooks 395a and 395b are coupled to the bottom of the expansion cone 315 for retrieving the over-expansion insert 330 during or after the completion of the radial expansion process.

After completing the plastic deformation and radial expansion of the tubular member 355, the hardenable fluidic sealing material is allowed to cure to thereby form an annular body 400 that provides a barrier to fluid flow into or out of the wellbore 10.

Referring to Fig. 2h, the shoe 340 may then removed by drilling out the shoe using a conventional drilling device. A new section of the wellbore 10 may also be drilled out in order to permit additional expandable tubular members to be coupled to the bottom portion of the plastically deformed and radially expanded tubular member 355.

Referring to Fig. 2j, a tubular member 405 may then be plastically deformed and radially expanded using any number of conventional methods of radially expanding a tubular member. In a preferred embodiment, the upper portion of the radially expanded tubular member 405 overlaps with and mates with the recessed portion 390 of the tubular member 355. In a preferred embodiment, one or more sealing members 410 are coupled to the exterior surface of the upper portion of the tubular member 405. In a preferred embodiment, the sealing members 410 seal the interface between the upper portion of the tubular member 405 and the recessed portion 390 of the tubular member 355. In several alternative embodiments, the sealing members 410 may include elastomeric elements and/or metallic elements and/or composite elements. In several alternative embodiments, one or more anchoring elements may substituted for, or used in addition to, the sealing members 410. In a preferred embodiment, an annular body 415 of a hardenable fluidic sealing material is also formed around the tubular member 405 using one or more conventional methods.

In a preferred embodiment, the tubular member 405 is plastically deformed and radially expanded, and the annular body 415 is formed using one or more of the apparatus and methods disclosed in the following: (1) U.S. patent 6497289, (2) Australian patent application AU-A-16417/00, (3) U.S. patent 6823937, (4) U.S. patent 6328113, (5) U.S. patent 6640903, (6) U.S. patent 6568471, (7) U.S. patent 6575240, (8) U.S. patent 6557640, (9) U.S. patent 6604763, (10) International patent application WO 01/04535, (11) International patent application WO 01/33037, (12) U.S. patent 6564875, (13) U.S. patent 6695012, (14) U.S. patent application US-A-2003-0121558, (15) U.S. patent application US-A-2004-0033906, (16) U.S. patent application US-A-2003-0116325, and (17) U.S. patent application US-A-2004-0045718, the disclosures of which are incorporated herein by reference.

In an alternative embodiment, the annular body 415 may be omitted. In several alternative embodiments, the annular body 415 may be radially compressed before, during and/or after curing.

Referring to Fig. 2j, an expansion cone 420 may then be driven in a downward direction by fluid pressure and/or by a support member 425 to plastically deform and radially expand the tubular member 405 such that the interior diameter of the tubular members 355 and 405 are substantially equal. In this manner, as illustrated in Fig. 2k, a mono-diameter wellbore casing may be formed.

Referring to Figs 5a-5b, in an alternative embodiment, a tubular member 500 having a shoe 505 may be plastically deformed and radially expanded and thereby coupled to the preexisting section of wellbore casing 15 using any number of conventional methods. An annular body of a fluidic sealing material 510 may also be formed around the tubular member 500 using any number of conventional methods. In a preferred embodiment, the tubular member 500 is plastically deformed and radially expanded and the annular body 510 is formed using one or more of the methods and apparatus disclosed in one or more of the following: (1) U.S. patent 6497289, (2) Australian patent application AU-A-16417/00, (3) U.S. patent 6823937, (4) U.S. patent 6328113, (5) U.S. patent 6640903, (6) U.S. patent 6568471, (7) U.S. patent 6575240,

2001294802 06 Oct 2005

(8) U.S. patent 6557640, (9) U.S. patent 6604763, (10) International patent application WO 01/04535, (11) International patent application WO 01/33037, (12) U.S. patent 6564875, (13) U.S. patent 6695012, (14) U.S. patent application US-A-2003-0121558, (15) U.S. patent application US-A-2004-0033906, (16) U.S. patent application US-A-2003-0116325, and (17) U.S. patent application US-A-2004-0045718, the disclosures of which are incorporated herein by reference.

In several alternative embodiments, the annular body 510 may be omitted or may be compressible before, during, or after curing.

Referring to Figs. 5c and 5d, a conventional inflatable bladder 515 may then be positioned within the tubular member 500 and inflated to a sufficient operating pressure to plastically deform and radially expand a portion of the tubular member to thereby form a recess 520 in the tubular member.

Referring to Figs. 5e and 5f, the inflatable bladder 515 may then be removed and the shoe 505 drilled out using a conventional drilling device.

Referring to Fig. 5g, an additional tubular member 525 may then be plastically deformed and radially expanded in a conventional manner and/or by using one or more of the methods and apparatus described above in order to form a mono-diameter wellbore casing. Before, during or after the radial expansion of the tubular member 525, an annular body 530 of a fluidic sealing material may be formed around the tubular member in a conventional manner and/or by using one or more of the methods and apparatus described above.

In several alternative embodiments, the inflatable bladder 515 may be coupled to the bottom of an expansion cone in order to permit the over-expansion process to be performed during the radial expansion process implemented using the expansion cone.

Referring to Figs 6a-6b, in an alternative embodiment, a tubular member 600 having a shoe 605 may be plastically deformed and radially expanded and thereby coupled to the preexisting section of wellbore casing 15 using any number of conventional methods. An annular body of a fluidic sealing material 610 may also be formed around the tubular member 600 using any number of conventional methods. In

2001294802 06 Oct 2005

a preferred embodiment, the tubular member 600 is plastically deformed and radially expanded and the annular body 610 is formed using one or more of the methods and apparatus disclosed in one or more of the following: (1) U.S. patent 6497289, (2) Australian patent application AU-A-16417/00, (3) U.S. patent 6823937, (4) U.S. patent 6328113, (5) U.S. patent 6640903, (6) U.S. patent 6568471, (7) U.S. patent 6575240, (8) U.S. patent 6557640, (9) U.S. patent 6604763, (10) International patent application WO 01/04535, (11) International patent application WO 01/33037, (12) U.S. patent 6564875, (13) U.S. patent 6695012, (14) U.S. patent application US-A-2003-0121558, (15) U.S. patent application US-A-2004-0033906, (16) U.S. patent application US-A-2003-0116325, and (17) U.S. patent application US-A-2004-0045718, the disclosures of which are incorporated herein by reference.

In several alternative embodiments, the annular body 610 may be omitted or may be compressible before, during, or after curing.

Referring to Figs. 6c and 6d, a conventional roller expansion device 615 may then be positioned within the tubular member 600 and operated in a conventional manner apply a radial force to the interior surface of the tubular member 600 to plastically deform and radially expand a portion of the tubular member to thereby form a recess 620 in the tubular member. As will be recognized by persons having ordinary skill in the art, a roller expansion device typically utilizes one or more rollers that, through rotation of the device, apply a radial force to the interior surfaces of a tubular member. In several alternative embodiments, the roller expansion device 615 may include eccentric rollers such as, for example, as disclosed in U.S. Pat. Nos. 5,014,779 and 5,083,608, the disclosures of which are incorporated herein by reference.

Referring to Figs. 6d and 6e, the roller expansion device 615 may then be removed and the shoe 605 drilled out using a conventional drilling device.

Referring to Fig. 6f, an additional tubular member 625 may then be plastically deformed and radially expanded in a conventional manner and/or by using one or more of the methods and apparatus described above in order to form a mono-diameter wellbore casing. Before, during or after the radial expansion of the tubular member

625, an annular body 630 of a fluidic sealing material may be formed around the tubular member in a conventional manner and/or by using one or more of the methods and apparatus described above.

5 In several alternative embodiments, the roller expansion device 615 may be coupled to the bottom of an expansion cone in order to permit the over-expansion process to be performed during the radial expansion process implemented using the expansion cone.

Referring initially to Fig. 7a, a wellbore 10 includes a preexisting wellbore casing 15. The wellbore 10 may be oriented in any orientation from the vertical to the horizontal. The preexisting wellbore casing 15 may be coupled to the upper portion of the wellbore 10 using any number of conventional methods. In a preferred embodiment, the wellbore casing 15 is coupled to the upper portion of the wellbore 10 using one or more of the methods and apparatus disclosed in one or more of the following: (1) U.S. patent 6497289, (2) Australian patent application AU-A-16417/00, 15 (3) U.S. patent 6823937, (4) U.S. patent 6328113, (5) U.S. patent 6640903, (6) U.S. patent 6568471, (7) U.S. patent 6575240, (8) U.S. patent 6557640, (9) U.S. patent 6604763, (10) International patent application WO 01/04535, (11) International patent application WO 01/33037, (12) U.S. patent 6564875, (13) U.S. patent 6695012, (14) U.S. patent application US-A-2003-0121558, (15) U.S. patent application US-A-2004- 20 0033906, (16) U.S. patent application US-A-2003-0116325, and (17) U.S. patent application US-A-2004-0045718, the disclosures of which are incorporated herein by reference. More generally, the preexisting wellbore casing 15 may be coupled to another preexisting wellbore casing and/or may include one or more concentrically positioned tubular members.

25 Referring to Fig. 7b, an apparatus 700 for radially expanding a tubular member may then be positioned within the wellbore 10. The apparatus 700 includes a tubular support member 705 defining a passage 710 for conveying fluidic materials. An expansion cone 715 defining a passage 720 and having an outer conical surface 725 for

2001294802 06 Oct 2005

radially expanding tubular members is coupled to an end of the tubular support member 705.

5 An expansion cone launcher 735 is movably coupled to and supported by the expansion cone 715. The expansion cone launcher 735 includes an upper portion 735a having an upper outer diameter, an intermediate portion 735b that mates with the expansion cone 715, and a lower portion 735c having a lower outer diameter. The lower outer diameter is greater than the upper outer diameter. The expansion cone launcher 735 further includes a recessed portion 735d having an outer diameter that is less than the lower outer diameter.

10 A shoe 740 defining a valveable passage 745 is coupled to the lower portion of the expansion cone launcher 735. In a preferred embodiment, the valveable passage 745 may be controllably closed in order to fluidically isolate a region 750 below the expansion cone 715 and bounded by the lower portion 735c of the expansion cone launcher 735 and the shoe 740 from the region outside of the apparatus 700.

15 An expandable tubular member 755 is coupled to the upper portion 735a of the expansion cone launcher 735. One or more sealing members 760a and 760b may be coupled to the exterior of the upper portion of the expandable tubular member 755. In several alternative embodiments, the sealing members 760a and 760b may include elastomeric elements and/or metallic elements and/or composite elements. In several
20 alternative embodiments, one or more anchoring elements may substituted for, or used in addition to, the sealing members 760a and 760b.

In a preferred embodiment, the support member 705, the expansion cone 715, the expansion cone launcher 735, the shoe 740, and the expandable tubular member 755 are provided substantially as disclosed in one or more of the following: (1) U.S.
25 patent 6497289, (2) Australian patent application AU-A-16417/00, (3) U.S. patent 6823937, (4) U.S. patent 6328113, (5) U.S. patent 6640903, (6) U.S. patent 6568471, (7) U.S. patent 6575240, (8) U.S. patent 6557640, (9) U.S. patent 6604763, (10) International patent application WO 01/04535, (11) International patent application WO 01/33037, (12) U.S. patent 6564875, (13) U.S. patent 6695012, (14) U.S. patent

application US-A-2003-0121558, (15) U.S. patent application US-A-2004-0033906, (16) U.S. patent application US-A-2003-0116325, and (17) U.S. patent application US-A-2004-0045718, the disclosures of which are incorporated herein by reference.

As illustrated in Fig. 7b, in a preferred embodiment, during placement of the apparatus 700 within the wellbore 10, fluidic materials 765 within the wellbore 10 are conveyed through the apparatus 700 through the passages 710, 720 and 745 to a location above the apparatus 700. In this manner, surge pressures during placement of the apparatus 700 within the wellbore 10 are reduced. In a preferred embodiment, the apparatus 700 is initially positioned within the wellbore 10 such that the top portion of the tubular member 755 overlaps with the preexisting casing 15. In this manner, the upper portion of the expandable tubular member 755 may be radially expanded into contact with and coupled to the preexisting casing 15. As will be recognized by persons having ordinary skill in the art, the precise initial position of the expandable tubular member 755 will vary as a function of the amount of radial expansion, the amount of axial shrinkage during radial expansion, and the material properties of the expandable tubular member.

As illustrated in Fig. 7c, a fluidic material 770 may then be injected through the apparatus 700 through the passages 710, 720, and 745 in order to test the proper operation of these passages.

As illustrated in Fig. 7d, a hardenable fluidic sealing material 775 may then be injected through the apparatus 700 through the passages 710, 720 and 745 into the annulus between the apparatus and the wellbore 10. In this manner, an annular barrier to fluid migration into and out of the wellbore 10 may be formed around the radially expanded expansion cone launcher 735 and expandable tubular member 755. The hardenable fluidic sealing material may include, for example, a cement mixture. In several alternative

- 34 -

2001294802 06 Oct 2005

This page is left intentionally blank

2001294802 06 Oct 2005

body 915 may be provided using any number of conventional methods, the methods described above, and/or using one or more of the methods disclosed in the following: (1) U.S. patent 6497289, (2) Australian patent application AU-A-16417/00, (3) U.S. patent 6823937, (4) U.S. patent 6328113, (5) U.S. patent 6640903, (6) U.S. patent 5 6568471, (7) U.S. patent 6575240, (8) U.S. patent 6557640, (9) U.S. patent 6604763, (10) International patent application WO 01/04535, (11) International patent application WO 01/33037, (12) U.S. patent 6564875, (13) U.S. patent 6695012, (14) U.S. patent application US-A-2003-0121558, (15) U.S. patent application US-A-2004-0033906, (16) U.S. patent application US-A-2003-0116325, and (17) U.S. patent 10 application US-A-2004-0045718, the disclosures of which are incorporated herein by reference.

Referring to Fig. 8b, an apparatus 1000 for radially expanding a tubular member is then positioned within the wellbore 10 that includes a tubular support member 1005 that defines a passage 1010 for conveying fluidic materials. A hydraulic locking 15 device 1015 that defines a passage 1020 for conveying fluidic materials that is fluidically coupled to the

elastomeric elements and/or metallic elements and/or composite elements. In several alternative embodiments, one or more anchoring elements may substituted for, or used in addition to, the sealing members.

5 An expansion cone 1085 defining a passage 1090 for receiving the tubular support member 1005 includes an outer conical surface 1095. A tubular support member 1100 defining a passage 1105 for receiving the tubular support member 1005 is coupled to the bottom of the expansion cone 1085 for supporting and actuating the expansion cone.

In a preferred embodiment, the support members 1005 and 1035, the expansion
10 cone 1045, the expansion cone launcher 1060, the shoe 1065, and the expandable tubular member 1080 are provided substantially as disclosed in one or more of the following: (1) U.S. patent 6497289, (2) Australian patent application AU-A-16417/00, (3) U.S. patent 6823937, (4) U.S. patent 6328113, (5) U.S. patent 6640903, (6) U.S. patent 6568471, (7) U.S. patent 6575240, (8) U.S. patent 6557640, (9) U.S. patent
15 6604763, (10) International patent application WO 01/04535, (11) International patent application WO 01/33037, (12) U.S. patent 6564875, (13) U.S. patent 6695012, (14) U.S. patent application US-A-2003-0121558, (15) U.S. patent application US-A-2004-0033906, (16) U.S. patent application US-A-2003-0116325, and (17) U.S. patent application US-A-2004-0045718, the disclosures of which are incorporated herein by
20 reference.

As illustrated in Fig. 8b, in a preferred embodiment, during placement of the apparatus 1000 within the wellbore 10, fluidic materials 1110 within the wellbore 10 are conveyed through the apparatus 1000 through the passages 1010, 1020, 1040 and 1070 to a location above the apparatus 1000. In this manner, surge pressures during
25 placement of the apparatus 1000 within the wellbore 10 are reduced. In a preferred embodiment, the apparatus 1000 is initially positioned within the wellbore 10 such that the top portion of the tubular member 1080 overlaps with the recess 910 of the preexisting casing 900. In this manner, the upper portion of the expandable tubular

2001294802 06 Oct 2005

member 1080 may be radially expanded into contact with and coupled to the recess 910 of the preexisting casing 900.

As illustrated in Fig. 8c, a fluidic material 1115 may then be injected through the apparatus 1000 through the passages 1010, 1020, 1040, and 1070 in order to test the proper operation of these passages.

As illustrated in Fig. 8d, a hardenable fluidic sealing material 1120 may then be injected through the apparatus 1000 through the passages 1010, 1020, 1040, and 1070 into the annulus between the apparatus and the wellbore 10. In this manner, an annular barrier to fluid migration into and out of the wellbore 10 may be formed around the radially expanded expansion cone launcher 1060 and expandable tubular member 1080. The hardenable fluidic sealing material may include, for example, a cement mixture. In several alternative embodiments, the injection of the hardenable fluidic sealing material 1120 may be omitted. In several alternative embodiments, the hardenable fluidic sealing material 1120 is compressible, before, during and/or after, the curing process.

As illustrated in Fig. 8e, a non-hardenable fluidic material 1125 may then be injected into the apparatus 1000 through the passages 1010, 1020 and 1040. A ball plug 1130, or other similar device, may then be injected with the fluidic material 1125 to thereby seal off the passage 1070. In this manner, the region 1075 may be pressurized by the continued injection of the fluidic material 1125 into the apparatus 1000. Furthermore, in this manner, the actuating chambers, 1025a and 1025b, of the locking device 1015 may

A wellbore casing formed in a wellbore has also been described that includes a plastically deformed and radially expanded first tubular member having a first portion having a first outside diameter and a remaining portion having a second outside diameter, and a plastically deformed and radially expanded second tubular member
5 coupled to the first portion of the first tubular member. The ratio of the original outside diameter OD_0 of the first tubular member to the original wall thickness t_0 of the first tubular member is greater than or equal to 16. In a preferred embodiment, the inside diameters of the first and second tubular members are substantially equal.

An apparatus has also been described that includes a plastically deformed and
10 radially expanded tubular member. In a preferred embodiment, the ratio of the original outside diameter OD_0 of the tubular member to the original wall thickness t_0 of the tubular member is greater than or equal to 16.

In several alternative embodiments, the methods and apparatus described and referenced above may be used to form or repair wellbore casings, pipelines, and
15 structural supports.

Although this detailed description has shown and described illustrative embodiments of the invention, this description contemplates a wide range of modifications, changes, and substitutions. In some instances, one may employ some features of the present invention without a corresponding use of the other features.
20 Accordingly, it is appropriate that readers should construe the appended claims broadly, and in a manner consistent with the scope of the invention.

Throughout this specification and the claims which follow, unless the context requires otherwise, the word "comprise", and variations such as "comprises" and "comprising", will be understood to imply the inclusion of a stated integer or step or
25 group of integers or steps but not the exclusion of any other integer or step or group of integers or steps.

The reference to any prior art in this specification is not, and should not be taken as, an acknowledgment or any form of suggestion that that prior art forms part of the common general knowledge in Australia.

2001294802 06 Oct 2005

THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. An apparatus for plastically deforming and radially expanding a tubular member, comprising:
 - 5 means for plastically deforming and radially expanding a first portion of the tubular member to a first outside diameter; and
 - means for plastically deforming and radially expanding a second portion of the tubular member to a second outside diameter;
 - wherein the means for plastically deforming and radially expanding the first portion
 - 10 of the tubular member to the first outside diameter is frangible.
2. An apparatus for plastically deforming and radially expanding a tubular member, comprising:
 - means for plastically deforming and radially expanding a first portion of the tubular
 - 15 member to a first outside diameter; and
 - means for plastically deforming and radially expanding a second portion of the tubular member to a second outside diameter;
 - wherein the means for plastically deforming and radially expanding the first portion
 - 20 of the tubular member to the first outside diameter is elastic.
3. An apparatus for plastically deforming and radially expanding a tubular member, comprising:
 - means for plastically deforming and radially expanding a first portion of the tubular
 - member to a first outside diameter; and
 - 25 means for plastically deforming and radially expanding a second portion of the tubular member to a second outside diameter;
 - wherein the means for plastically deforming and radially expanding the first portion
 - of the tubular member to the first outside diameter is inflatable.
- 30 4. An apparatus for plastically deforming and radially expanding a tubular member, comprising:

means for plastically deforming and radially expanding a first portion of the tubular member to a first outside diameter; and

means for plastically deforming and radially expanding a second portion of the tubular member to a second outside diameter;

5 wherein the means for plastically deforming and radially expanding the first portion of the tubular member to the first outside diameter includes rolling means for applying radial pressure to the first portion of the tubular member.

5. An apparatus for plastically deforming and radially expanding a tubular member,
10 comprising:

a tubular support member including a first fluid passage;

an expansion cone coupled to the tubular support member having a second fluid passage fluidically coupled to the first fluid passage and an outer conical surface;

15 a removable annular conical sleeve coupled to the outer conical surface of the expansion cone;

an annular expansion cone launcher coupled to the conical sleeve and a lower portion of the tubular member; and

a shoe having a valveable passage coupled to an end of the expansion cone launcher.

20

6. The apparatus of claim 5, wherein the conical sleeve is frangible.

7. The apparatus of claim 5, wherein the conical sleeve is elastic.

25 8. The apparatus of claim 5, wherein the conical sleeve comprises a plurality of arcuate elements.

9. A method of plastically deforming and radially expanding a tubular member,
comprising:

30 plastically deforming and radially expanding a portion of the tubular member to a first outside diameter; and

2001294802 06 Oct 2005

plastically deforming and radially expanding another portion of the tubular member to a second outside diameter;

wherein plastically deforming and radially expanding the portion of the tubular member comprises:

5 applying a radial force to the portion of the tubular member using a conical sleeve.

10. The method of claim 9, wherein the conical sleeve is frangible.

11. The method of claim 9, wherein the conical sleeve is elastic.

10

12. The method of claim 9, wherein the conical sleeve comprises a plurality of arcuate elements.

13. A method of plastically deforming and radially expanding a tubular member, comprising:

15

plastically deforming and radially expanding a portion of the tubular member to a first outside diameter; and

plastically deforming and radially expanding another portion of the tubular member to a second outside diameter;

20 wherein plastically deforming and radially expanding the portion of the tubular member comprises:

applying a radial force to the portion of the tubular member using an inflatable bladder.

25 14. A method of plastically deforming and radially expanding a tubular member, comprising:

plastically deforming and radially expanding a portion of the tubular member to a first outside diameter; and

30 plastically deforming and radially expanding another portion of the tubular member to a second outside diameter;

wherein plastically deforming and radially expanding the portion of the tubular

2001294802 06 Oct 2005

member comprises:

applying a radial force to the portion of the tubular member using a roller expansion device.

- 5 15. A method of coupling a first tubular member to a second tubular member, comprising:

plastically deforming and radially expanding a first portion of the first tubular member to a first outside diameter;

- 10 plastically deforming and radially expanding another portion of the first tubular member to a second outside diameter;

positioning the second tubular member inside the first tubular member in overlapping relation to the first portion of the first tubular member;

plastically deforming and radially expanding the second tubular member to a third outside diameter; and

- 15 plastically deforming and radially expanding the second tubular member to a fourth outside diameter;

wherein the first and second tubular members after the plastic deformations and radial expansions define a passage having a constant cross sectional area.

- 20 16. The method of claim 15, wherein the first outside diameter is greater than the second outside diameter.

17. The method of claim 15, wherein plastically deforming and radially expanding the first portion of the first tubular member comprises:

- 25 applying a radial force to the portion of the tubular member using a conical sleeve.

18. The method of claim 17, wherein the conical sleeve is frangible.

19. The method of claim 17, wherein the conical sleeve is elastic.

30

20. The method of claim 17, wherein the conical sleeve comprises a plurality of arcuate

elements.

21. The method of claim 15, wherein plastically deforming and radially expanding the first portion of the first tubular member comprises:

5 applying a radial force to the first portion of the first tubular member using an inflatable bladder.

22. The method of claim 15, wherein plastically deforming and radially expanding the first portion of the first tubular member comprises:

10 applying a radial force to the first portion of the first tubular member using a roller expansion device.

23. An apparatus for coupling a first tubular member to a second tubular member, comprising:

15 means for plastically deforming and radially expanding a first portion of the first tubular member to a first outside diameter;

 means for plastically deforming and radially expanding another portion of the first tubular member to a second outside diameter;

 means for positioning the second tubular member inside the first tubular member in overlapping relation to the first portion of the first tubular member;

20 means for plastically deforming and radially expanding the second tubular member to a third outside diameter; and

 means for plastically deforming and radially expanding the second tubular member to a fourth outside diameter;

25 wherein the first and second tubular members after the plastic deformations and radial expansions define a passage having a constant cross sectional area.

24. The apparatus of claim 23, wherein the first outside diameter is greater than the second outside diameter.

30

25. The apparatus of claim 23, wherein the means for plastically deforming and

2001294802 06 Oct 2005

a removable annular conical sleeve coupled to the outer conical surface of the expansion cone;

an annular expansion cone launcher coupled to the conical sleeve and a lower portion of the tubular member; and

5 a shoe having a valveable passage coupled to an end of the expansion cone launcher.

36. The apparatus of claim 35, wherein the conical sleeve is frangible.

10 37. The apparatus of claim 35, wherein the conical sleeve is elastic.

38. The apparatus of claim 35, wherein the conical sleeve comprises a plurality of arcuate elements.

15 39. A method of forming a wellbore casing within a wellbore, comprising:
supporting a tubular member within a wellbore;

plastically deforming and radially expanding a portion of the tubular member to a first outside diameter; and

20 plastically deforming and radially expanding another portion of the tubular member to a second outside diameter;

wherein plastically deforming and radially expanding the portion of the tubular member comprises:

25 applying a radial force to the portion of the tubular member using a conical sleeve.

40. The method of claim 39, wherein the conical sleeve is frangible.

41. The method of claim 39, wherein the conical sleeve is elastic.

30 42. The method of claim 39, wherein the conical sleeve comprises a plurality of arcuate elements.

2001294802 06 Oct 2005

43. A method of forming a wellbore casing within a wellbore, comprising:
 supporting a tubular member within a wellbore;
 plastically deforming and radially expanding a portion of the tubular member to a
 5 first outside diameter; and
 plastically deforming and radially expanding another portion of the tubular member
 to a second outside diameter;
 wherein plastically deforming and radially expanding the portion of the tubular
 member comprises:
 10 applying a radial force to the portion of the tubular member using an inflatable
 bladder.
44. A method of forming a wellbore casing within a wellbore, comprising:
 supporting a tubular member within a wellbore;
 15 plastically deforming and radially expanding a portion of the tubular member to a
 first outside diameter; and
 plastically deforming and radially expanding another portion of the tubular member
 to a second outside diameter;
 wherein plastically deforming and radially expanding the portion of the tubular
 20 member comprises:
 applying a radial force to the portion of the tubular member using a roller
 expansion device.
45. A method of forming a mono-diameter wellbore casing within a wellbore,
 25 comprising:
 supporting a first tubular member within the wellbore;
 plastically deforming and radially expanding a first portion of the first tubular
 member to a first outside diameter;
 plastically deforming and radially expanding another portion of the first tubular
 30 member to a second outside diameter;
 positioning the second tubular member inside the first tubular member in

overlapping relation to the radially expanded first portion of the first tubular member;

plastically deforming and radially expanding the second tubular member to a third outside diameter; and

5 plastically deforming and radially expanding the second tubular member to a fourth outside diameter;

wherein the first and second tubular members after the plastic deformations and radial expansions define a passage having a constant cross sectional area.

46. The method of claim 45, wherein the first outside diameter is greater than the
10 second outside diameter.

47. The method of claim 45, wherein plastically deforming and radially expanding the first portion of the first tubular member comprises:

15 applying a radial force to the portion of the tubular member using a conical sleeve.

48. The method of claim 47, wherein the conical sleeve is frangible.

49. The method of claim 47, wherein the conical sleeve is elastic.

20 50. The method of claim 47, wherein the conical sleeve comprises a plurality of arcuate elements.

51. The method of claim 45, wherein plastically deforming and radially expanding the first portion of the first tubular member comprises:

25 applying a radial force to the first portion of the first tubular member using an inflatable bladder.

52. The method of claim 45, wherein plastically deforming and radially expanding the first portion of the first tubular member comprises:

30 applying a radial force to the first portion of the first tubular member using a roller expansion device.

53. The method of claim 45, further comprising:
injecting an annular body of a hardenable fluidic sealing material into an annulus
between the first tubular member and the wellbore.
- 5 54. The method of claim 45, further comprising:
injecting an annular body of a hardenable fluidic sealing material into an annulus
between the second tubular member and the wellbore.
- 10 55. The method of claim 53 or 54, further comprising:
curing the annular body of hardenable fluidic sealing material.
56. An apparatus for coupling a first tubular member to a second tubular member,
comprising:
- 15 means for plastically deforming and radially expanding a first portion of the first
tubular member to a first outside diameter;
means for plastically deforming and radially expanding another portion of the first
tubular member to a second outside diameter;
means for positioning the second tubular member inside the first tubular member in
20 overlapping relation to the radially expanded first portion of the first tubular member;
means for plastically deforming and radially expanding the second tubular member
to a third outside diameter; and
means for plastically deforming and radially expanding the second tubular member
to a fourth outside diameter;
- 25 wherein the first and second tubular members after the plastic deformations and
radial expansions define a passage having a constant cross sectional area.
57. The apparatus of claim 56, wherein the first outside diameter is greater than the
second outside diameter.

30

2001294802 06 Oct 2005

P:\O\ETP\04\001\294802 1 up.doc 03/10/05

58. The apparatus of claim 56, wherein the means for plastically deforming and radially expanding the first portion of the first tubular member comprises:
means for applying a radial force to the portion of the tubular member using a conical sleeve.
59. The apparatus of claim 58, wherein the conical sleeve is frangible.
60. The apparatus of claim 58, wherein the conical sleeve is elastic.
- 10 61. The apparatus of claim 58, wherein the conical sleeve comprises a plurality of arcuate elements.
62. The apparatus of claim 56, wherein the means for plastically deforming and radially expanding the first portion of the first tubular member comprises:
15 means for applying a radial force to the first portion of the first tubular member using an inflatable bladder.
63. The apparatus of claim 56, wherein the means for plastically deforming and radially expanding the first portion of the first tubular member comprises:
20 means for applying a radial force to the first portion of the first tubular member using a roller expansion device.
64. The apparatus of claim 56, further comprising:
means for injecting an annular body of a hardenable fluidic sealing material into an
25 annulus between the first tubular member and the wellbore.
65. The apparatus of claim 56, further comprising:
means for injecting an annular body of a hardenable fluidic sealing material into an
annulus between the second tubular member and the wellbore.
- 30 66. The apparatus of claim 64 or 65, further comprising:

means for curing the annular body of hardenable fluidic sealing material.

67. An apparatus for plastically deforming and radially expanding a tubular member, comprising:
- 5 means for providing a lipped portion in a portion of the tubular member; and
means for plastically deforming and radially expanding another portion of the tubular member.
68. An apparatus for plastically deforming and radially expanding a tubular member, comprising:
- 10 a tubular support member including a first fluid passage;
an expansion cone coupled to the tubular support member having a second fluid passage fluidly coupled to the first fluid passage and an outer conical surface;
an annular expansion cone launcher comprising:
- 15 a first annular portion coupled to a lower portion of the tubular member;
a second annular portion coupled to the first annular portion that mates with the outer conical surface of the expansion cone;
a third annular portion coupled to the second annular portion having a first outside diameter; and
- 20 a fourth annular portion coupled to the third annular portion having a second outside diameter;
wherein the second outside diameter is less than the first outside diameter; and
a shoe having a valveable passage coupled to fourth annular portion of the expansion cone launcher.
- 25
69. A method of plastically deforming and radially expanding a tubular member, comprising:
- providing a lipped portion in a portion of the tubular member; and
plastically deforming and radially expanding another portion of the tubular
- 30 member.

2001294802 06 Oct 2005

70. A method of coupling a first tubular member to a second tubular member, comprising:
- providing a lipped portion in a portion of the first tubular member;
 - plastically deforming and radially expanding another portion of the first tubular member;
 - 5 positioning the second tubular member inside the first tubular member in overlapping relation to the lipped portion of the first tubular member; and
 - plastically deforming and radially expanding the second tubular member;
 - wherein the inside diameters of the first and second tubular members after the
 - 10 plastic deformations and radial expansions are substantially equal.
71. An apparatus for coupling a first tubular member to a second tubular member, comprising:
- means for providing a lipped portion in the first tubular member;
 - 15 means for plastically deforming and radially expanding another portion of the first tubular member;
 - means for positioning the second tubular member inside the first tubular member in overlapping relation to the lipped portion of the first tubular member; and
 - means for plastically deforming and radially expanding the second tubular member;
 - 20 wherein the inside diameters of the first and second tubular members after the plastic deformations and radial expansions are substantially equal.
72. An apparatus for forming a wellbore casing within a wellbore, comprising:
- means for supporting a tubular member within the wellbore;
 - 25 means for providing a lipped portion in the tubular member; and
 - means for plastically deforming and radially expanding another portion of the tubular member to a second outside diameter.
73. An apparatus for forming a wellbore casing within a wellbore, comprising:
- 30 a tubular support member including a first fluid passage;

an expansion cone coupled to the tubular support member having a second fluid passage fluidically coupled to the first fluid passage and an outer conical surface;

an annular expansion cone launcher comprising:

a first annular portion coupled to a lower portion of the tubular member;

5 a second annular portion coupled to the first annular portion that mates with the outer conical surface of the expansion cone;

a third annular portion coupled to the second annular portion having a first outside diameter; and

10 a fourth annular portion coupled to the third annular portion having a second outside diameter;

wherein the second outside diameter is less than the first outside diameter; and

a shoe having a valveable passage coupled to fourth annular portion of the expansion cone launcher.

15 74. A method of forming a wellbore casing in a wellbore, comprising:

supporting a tubular member within the wellbore;

providing a lipped portion in a portion of the tubular member; and

plastically deforming and radially expanding another portion of the tubular member.

20

75. The method of claim 74, further comprising:

injecting a hardenable fluidic sealing material in an annulus between the tubular member and the wellbore.

25 76. The method of claim 75, further comprising:

curing the fluidic sealing material.

77. A method of forming a mono-diameter wellbore casing within a wellbore, comprising:

30 supporting a first tubular member within the wellbore;

providing a lipped portion in a portion of the first tubular member;

2001294802 06 Oct 2005

plastically deforming and radially expanding another portion of the first tubular member;

positioning the second tubular member inside the first tubular member in overlapping relation to the lipped portion of the first tubular member; and

- 5 plastically deforming and radially expanding the second tubular member;
 wherein the inside diameters of the first and second tubular members after the plastic deformations and radial expansions are substantially equal.

78. The method of claim 77, further comprising:

- 10 injecting a hardenable fluidic sealing material in an annulus between the first tubular member and the wellbore.

79. The method of claim 77, further comprising:

- 15 injecting a hardenable fluidic sealing material in an annulus between the second tubular member and the wellbore.

80. The method of claim 78 or 79, further comprising:

 curing the fluidic sealing material.

- 20 81. An apparatus for forming a mono-diameter wellbore casing within a wellbore, comprising:

 means for providing a lipped portion in the first tubular member;

 means for plastically deforming and radially expanding another portion of the first tubular member;

- 25 means for positioning the second tubular member inside the first tubular member in overlapping relation to the lipped portion of the first tubular member; and

 means for plastically deforming and radially expanding the second tubular member;

 wherein the inside diameters of the first and second tubular members after the plastic deformations and radial expansions are substantially equal.

30

82. The apparatus of claim 81, further comprising:

means for injecting a hardenable fluidic sealing material in an annulus between the first tubular member and the wellbore.

83. The apparatus of claim 81, further comprising:

5 means for injecting a hardenable fluidic sealing material in an annulus between the second tubular member and the wellbore.

84. The apparatus of claim 82 or 83, further comprising:

means for curing the fluidic sealing material.

10

85. An apparatus for plastically deforming and radially expanding a tubular member, comprising:

a tubular support member including a first passage;

an expansion cone coupled to the tubular support having a second passage fluidically

15 coupled to the first passage and an outer conical surface;

an annular expansion cone launcher movably coupled to outer conical surface of the expansion cone;

an expandable tubular member coupled to an end of the annular expansion cone launcher;

20 a shoe coupled to another end of the annular expansion cone launcher having a valveable fluid passage; and

another annular expansion cone movably coupled to the tubular support member; wherein the annular expansion cones are positioned in opposite orientations.

25 86. The apparatus of claim 85, wherein the annular expansion cone is adapted to plastically deform and radially expand a first end of the expandable tubular member and the other annular expansion cone is adapted to plastically deform and radially expand a second end of the expandable tubular member.

30 87. The apparatus of claim 85, further comprising:

2001294802 06 Oct 2005

an anchoring member coupled to the tubular support member adapted to hold the expandable tubular.

88. An apparatus for forming a wellbore casing within a wellbore, comprising:
- 5 a tubular support member including a first passage;
 - an expansion cone coupled to the tubular support having a second passage fluidically coupled to the first passage and an outer conical surface;
 - an annular expansion cone launcher movably coupled to outer conical surface of the expansion cone;
 - 10 an expandable tubular member coupled to an end of the annular expansion cone launcher;
 - a shoe coupled to another end of the annular expansion cone launcher having a valveable fluid passage; and
 - another annular expansion cone movably coupled to the tubular support member;
 - 15 wherein the annular expansion cones are positioned in opposite orientations.

89. The apparatus of claim 88, wherein the annular expansion cone is adapted to plastically deform and radially expand a first end of the expandable tubular member and the other annular expansion cone is adapted to plastically deform and radially expand a
- 20 second end of the expandable tubular member.

90. The apparatus of claim 88, further comprising:
- an anchoring member coupled to the tubular support member adapted to hold the expandable tubular.

91. An apparatus for bridging an axial gap between opposing pairs of wellbore casing within a wellbore, comprising:
- means for supporting a tubular member in overlapping relation to the opposing ends of the wellbore casings;
 - 30 means for plastically deforming and radially expanding the tubular member; and

means for plastically deforming and radially expanding the tubular member and the opposing ends of the wellbore casings.

92. A method of bridging an axial gap between opposing pairs of wellbore casing
 5 within a wellbore, comprising:
 supporting a tubular member in overlapping relation to the opposing ends of the
 wellbore casings;
 plastically deforming and radially expanding the tubular member; and
 plastically deforming and radially expanding the tubular member and the opposing
 10 ends of the wellbore casings.

93. A method of forming a structure having desired strength characteristics,
 comprising:
 providing a first tubular member; and
 15 plastically deforming and radially expanding additional tubular members onto the
 interior surface of the first tubular member until the desired strength characteristics are
 achieved.

94. A method of forming a wellbore casing within a wellbore having desired strength
 20 characteristics, comprising:
 plastically deforming and radially expanding a first tubular member within the
 wellbore; and
 plastically deforming and radially expanding additional tubular members onto the
 interior surface of the first tubular member until the desired strength characteristics are
 25 achieved.

95. A method of coupling a first tubular member to a second tubular member, the first
 tubular member having an original outside diameter OD_0 and an original wall thickness t_0 ,
 comprising:
 30 plastically deforming and radially expanding a first portion of the first tubular
 member to a first outside diameter;

2001294802 06 Oct 2005

plastically deforming and radially expanding another portion of the first tubular member to a second outside diameter;

positioning the second tubular member inside the first tubular member in overlapping relation to the first portion of the first tubular member;

5 plastically deforming and radially expanding the second tubular member to a third outside diameter; and

plastically deforming and radially expanding the second tubular member to a fourth outside diameter;

10 wherein the inside diameters of the first and second tubular members after the plastic deformations and radial expansions are substantially equal; and

wherein the ratio of the original outside diameter OD_0 of the first tubular member to the original wall thickness t_0 of the first tubular member is greater than or equal to 16.

96. A method of forming a mono-diameter wellbore casing, comprising:

15 positioning a first tubular member within a wellbore, the first tubular member having an original outside diameter OD_0 and an original wall thickness t_0 ;

plastically deforming and radially expanding a first portion of the first tubular member to a first outside diameter;

20 plastically deforming and radially expanding another portion of the first tubular member to a second outside diameter;

positioning the second tubular member inside the first tubular member in overlapping relation to the first portion of the first tubular member;

plastically deforming and radially expanding the second tubular member to a third outside diameter; and

25 plastically deforming and radially expanding the second tubular member to a fourth outside diameter;

wherein the inside diameters of the first and second tubular members after the plastic deformations and radial expansions are substantially equal; and

30 wherein the ratio of the original outside diameter OD_0 of the first tubular member to the original wall thickness t_0 of the first tubular member is greater than or equal to 16.

2001294802 06 Oct 2005

97. An apparatus, comprising:
a plastically deformed and radially expanded tubular member having a first portion having a first outside diameter and a remaining portion having a second outside diameter, wherein the ratio of the original outside diameter OD_0 of the first tubular member to the original wall thickness t_0 of the first tubular member is greater than or equal to 16.
98. An apparatus, comprising:
a plastically deformed and radially expanded first tubular member having a first portion having a first outside diameter and a remaining portion having a second outside diameter; and
a plastically deformed and radially expanded second tubular member coupled to the first portion of the first tubular member;
wherein the ratio of the original outside diameter OD_0 of the first tubular member to the original wall thickness t_0 of the first tubular member is greater than or equal to 16.
99. The apparatus of claim 98, wherein the inside diameters of the first and second tubular members are substantially equal.
100. A wellbore casing formed in a wellbore, comprising:
a plastically deformed and radially expanded first tubular member having a first portion having a first outside diameter and a remaining portion having a second outside diameter; and
a plastically deformed and radially expanded second tubular member coupled to the first portion of the first tubular member;
wherein the ratio of the original outside diameter OD_0 of the first tubular member to the original wall thickness t_0 of the first tubular member is greater than or equal to 16.
101. The casing of claim 100, wherein the inside diameters of the first and second tubular members are substantially equal.
102. An apparatus, comprising:

a plastically deformed and radially expanded tubular member;
wherein the ratio of the original outside diameter OD_0 of the tubular member to the original wall thickness t_0 of the tubular member is greater than or equal to 16.

5 103. An apparatus for plastically deforming and radially expanding a tubular member, comprising:

means for coupling a first expansion cone to a second expansion cone;

means for plastically deforming and radially expanding a first portion of the tubular member to a first outside diameter using the first and second expansion cones;

10 means for plastically deforming and radially expanding a second portion of the tubular member to a second outside diameter using the second expansion cone; and

means for decoupling the first and second expansion cones prior to plastically deforming and radially expanding the second portion of the tubular member to the second outside diameter;

15 wherein the first outside diameter is greater than the second outside diameter.

104. A method of plastically deforming and radially expanding a tubular member, comprising:

20 plastically deforming and radially expanding a portion of the tubular member to a first outside diameter using a first expansion cone coupled to a second expansion cone;

decoupling the first and second expansion cones; and

plastically deforming and radially expanding another portion of the tubular member to a second outside diameter using the second expansion cone;

wherein the first outside diameter is greater than the second outside diameter.

25

105. A method of coupling a first tubular member to a second tubular member, comprising:

plastically deforming and radially expanding a first portion of the first tubular member to a first outside diameter using a first expansion cone coupled to a second

30 expansion cone;

decoupling the first and second expansion cones;

plastically deforming and radially expanding another portion of the first tubular member to a second outside diameter using the second expansion cone;

positioning the second tubular member inside the first tubular member in overlapping relation to the first portion of the first tubular member;

5 plastically deforming and radially expanding the second tubular member to a third outside diameter; and

plastically deforming and radially expanding the second tubular member to a fourth outside diameter;

wherein the first outside diameter is greater than the second outside diameter; and

10 wherein the inside diameters of the first and second tubular members after the plastic deformations and radial expansions are substantially equal.

106. An apparatus for coupling a first tubular member to a second tubular member, comprising:

15 means for plastically deforming and radially expanding a first portion of the first tubular member to a first outside diameter using a first expansion cone coupled to a second expansion cone;

means for decoupling the first expansion cone from the second expansion cone;

means for plastically deforming and radially expanding another portion of the first tubular member to a second outside diameter using the second expansion cone;

20 means for positioning the second tubular member inside the first tubular member in overlapping relation to the first portion of the first tubular member;

means for plastically deforming and radially expanding the second tubular member to a third outside diameter; and

25 means for plastically deforming and radially expanding the second tubular member to a fourth outside diameter;

wherein the first outside diameter is greater than the second outside diameter; and

wherein the inside diameters of the first and second tubular members after the plastic deformations and radial expansions are substantially equal.

30

107. An apparatus for forming a wellbore casing within a wellbore, comprising:

2001294802 06 Oct 2005

means for supporting a tubular member within the wellbore;
 means for plastically deforming and radially expanding a first portion of the tubular member to a first outside diameter using a first expansion cone coupled to a second expansion cone;

- 5 means for decoupling the first and second expansion cones; and
 means for plastically deforming and radially expanding a second portion of the tubular member to a second outside diameter using the second expansion cone;
 wherein the first outside diameter is greater than the second outside diameter.

- 10 108. A method of forming a wellbore casing within a wellbore, comprising:

supporting a tubular member within a wellbore;
 plastically deforming and radially expanding a portion of the tubular member to a first outside diameter using a first expansion cone coupled to a second expansion cone;
 decoupling the first and second expansion cones; and

- 15 plastically deforming and radially expanding another portion of the tubular member to a second outside diameter using the second expansion cone;
 wherein the first outside diameter is greater than the second outside diameter.

109. A method of forming a mono-diameter wellbore casing within a wellbore,

- 20 comprising:

supporting a first tubular member within the wellbore;
 plastically deforming and radially expanding a first portion of the first tubular member to a first outside diameter using a first expansion cone coupled to a second expansion cone;

- 25 decoupling the first and second expansion cones;
 plastically deforming and radially expanding another portion of the first tubular member to a second outside diameter using the second expansion cone;

positioning the second tubular member inside the first tubular member in overlapping relation to the first portion of the first tubular member;

- 30 plastically deforming and radially expanding the second tubular member to a third outside diameter; and

plastically deforming and radially expanding the second tubular member to a fourth outside diameter;

wherein the first outside diameter is greater than the second outside diameter; and

wherein the inside diameters of the first and second tubular members after the

5 plastic deformations and radial expansions are substantially equal.

110. Apparatus for coupling a first tubular member to a second tubular member, comprising:

10 means for plastically deforming and radially expanding a first portion of the first tubular member to a first outside diameter using a first expansion cone coupled to a second expansion cone;

means for decoupling the first and second expansion cones;

means for plastically deforming and radially expanding another portion of the first tubular member to a second outside diameter using the second expansion cone;

15 means for positioning the second tubular member inside the first tubular member in overlapping relation to the first portion of the first tubular member;

means for plastically deforming and radially expanding the second tubular member to a third outside diameter; and

20 means for plastically deforming and radially expanding the second tubular member to a fourth outside diameter;

wherein the first outside diameter is greater than the second outside diameter; and

wherein the inside diameters of the first and second tubular members after the plastic deformations and radial expansions are substantially equal.

25 111. Apparatus for plastically deforming and radially expanding and/or for coupling, substantially as herein described with reference to the accompanying drawings.

2001294802 06 Oct 2005

112. A method for plastically deforming and radially expanding and/or for coupling, substantially as herein described with reference to the accompanying drawings.

- 5 DATED this 5th day of October, 2005
Shell Internationale Research Maatschappij B.V.
By DAVIES COLLISON CAVE
Patent Attorneys for the Applicant

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record.

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☒ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.